


HISTORY OF MICROPROCESSORS



Gursharan Singh Tatla
 mailme@gursharansingh.in
 www.eazynotes.com

CONTENTS

- > Introduction
- > 4-Bit Microprocessors
- > 8-Bit Microprocessors
- > 16-Bit Microprocessors
- > 32-Bit Microprocessors
- > 64-Bit Microprocessors

Gursharan Singh Tatla
 mailme@gursharansingh.in

INTRODUCTION


- > Fairchild Semiconductors (founded in 1957) invented the first IC in 1959.
- > In 1968, **Robert Noyce, Gordon Moore, Andrew Grove** resigned from Fairchild Semiconductors.
- > They founded their own company **Intel** (Integrated Electronics).
- > Intel grown from 3 man start-up in 1968 to industrial giant by 1981.
- > It had 20,000 employees and \$188 million revenue.

Gursharan Singh Tatla
 mailme@gursharansingh.in

4-BIT MICROPROCESSORS

Gursharan Singh Tatla
 mailme@gursharansingh.in


INTEL 4004



- > Introduced in 1971.
- > It was the first microprocessor by Intel.
- > It was a 4-bit μ P.
- > Its clock speed was 740KHz.
- > It had 2,300 transistors.
- > It could execute around 60,000 instructions per second.

Gursharan Singh Tatla
 mailme@gursharansingh.in

INTEL 4040



- > Introduced in 1974.
- > It was also 4-bit μ P.

Gursharan Singh Tatla
 mailme@gursharansingh.in


8-BIT MICROPROCESSORS

7

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 8008



- > Introduced in 1972.
- > It was first 8-bit μ P.
- > Its clock speed was 500 KHz.
- > Could execute 50,000 instructions per second.

8

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 8080



- > Introduced in 1974.
- > It was also 8-bit μ P.
- > Its clock speed was 2 MHz.
- > It had 6,000 transistors.
- > Was 10 times faster than 8008.
- > Could execute 5,00,000 instructions per second.

9

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 8085



- > Introduced in 1976.
- > It was also 8-bit μ P.
- > Its clock speed was 3 MHz.
- > Its data bus is 8-bit and address bus is 16-bit.
- > It had 6,500 transistors.
- > Could execute 7,69,230 instructions per second.
- > It could access 64 KB of memory.
- > It had 246 instructions.
- > Over 100 million copies were sold.

10

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com


16-BIT MICROPROCESSORS

11

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 8086




- > Introduced in 1978.
- > It was first 16-bit μ P.
- > Its clock speed is 4.77 MHz, 8 MHz and 10 MHz, depending on the version.
- > Its data bus is 16-bit and address bus is 20-bit.
- > It had 29,000 transistors.
- > Could execute 2.5 million instructions per second.
- > It could access 1 MB of memory.
- > It had 22,000 instructions.
- > It had **Multiply** and **Divide** instructions.

12

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 8088




- > Introduced in 1979.
- > It was also 16-bit μ P.
- > It was created as a cheaper version of Intel's 8086.
- > It was a 16-bit processor with an 8-bit external bus.
- > Could execute 2.5 million instructions per second.
- > This chip became the most popular in the computer industry when IBM used it for its first PC.

13

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 80186 & 80188




- > Introduced in 1982.
- > They were 16-bit μ Ps.
- > Clock speed was 6 MHz.
- > 80188 was a cheaper version of 80186 with an 8-bit external data bus.
- > They had additional components like:
 - > Interrupt Controller
 - > Clock Generator
 - > Local Bus Controller
 - > Counters

14

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 80286



- > Introduced in 1982.
- > It was 16-bit μ P.
- > Its clock speed was 8 MHz.
- > Its data bus is 16-bit and address bus is 24-bit.
- > It could address 16 MB of memory.
- > It had 1,34,000 transistors.
- > It could execute 4 million instructions per second.

15

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com


32-BIT MICROPROCESSORS

16

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 80386




- > Introduced in 1986.
- > It was first 32-bit μ P.
- > Its data bus is 32-bit and address bus is 32-bit.
- > It could address 4 GB of memory.
- > It had 2,75,000 transistors.
- > Its clock speed varied from 16 MHz to 33 MHz depending upon the various versions.
- > Different versions:
 - > 80386 DX
 - > 80386 SX
 - > 80386 SL
- > Intel 80386 became the best selling microprocessor in history.

17

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL 80486




- > Introduced in 1989.
- > It was also 32-bit μ P.
- > It had 1.2 million transistors.
- > Its clock speed varied from 16 MHz to 100 MHz depending upon the various versions.
- > It had five different versions:
 - > 80486 DX
 - > 80486 SX
 - > 80486 DX2
 - > 80486 SL
 - > 80486 DX4
- > 8 KB of cache memory was introduced.

18

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com


INTEL PENTIUM



- Introduced in 1993.
- It was also 32-bit μ P.
- It was originally named 80586.
- Its clock speed was 66 MHz.
- Its data bus is 32-bit and address bus is 32-bit.
- It could address 4 GB of memory.
- Could execute 110 million instructions per second.
- Cache memory:
 - 8 KB for instructions.
 - 8 KB for data.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 19


INTEL PENTIUM PRO



- Introduced in 1995.
- It was also 32-bit μ P.
- It had L2 cache of 256 KB.
- It had 21 million transistors.
- It was primarily used in server systems.
- Cache memory:
 - 8 KB for instructions.
 - 8 KB for data.
- It had L2 cache of 256 KB.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 20


INTEL PENTIUM II



- Introduced in 1997.
- It was also 32-bit μ P.
- Its clock speed was 233 MHz to 500 MHz.
- Could execute 333 million instructions per second.
- MMX technology was supported.
- L2 cache & processor were on one circuit.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 21


INTEL PENTIUM II XEON



- Introduced in 1998.
- It was also 32-bit μ P.
- It was designed for servers.
- Its clock speed was 400 MHz to 450 MHz.
- L1 cache of 32 KB & L2 cache of 512 KB, 1MB or 2 MB.
- It could work with 4 Xeons in same system.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 22


INTEL PENTIUM III



- Introduced in 1999.
- It was also 32-bit μ P.
- Its clock speed varied from 500 MHz to 1.4 GHz.
- It had 9.5 million transistors.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 23


INTEL PENTIUM IV



- Introduced in 2000.
- It was also 32-bit μ P.
- Its clock speed was from 1.3 GHz to 3.8 GHz.
- L1 cache was of 32 KB & L2 cache of 256 KB.
- It had 42 million transistors.
- All internal connections were made from aluminium to copper.

www.eazynotes.com Gursharan Singh Tatla
mailto:gursharansingh.in 24

INTEL DUAL CORE




- > Introduced in 2006.
- > It is 32-bit or 64-bit μ P.
- > It has two cores.
- > Both the cores have their own internal bus and L1 cache, but share the external bus and L2 cache (Next Slide).
- > It supported SMT technology.
- > SMT: Simultaneously Multi-Threading
- > E.g.: Adobe Photoshop supported SMT.

25

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com




64-BIT MICROPROCESSORS

27

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL CORE 2




- > Introduced in 2006.
- > It is a 64-bit μ P.
- > Its clock speed is from 1.2 GHz to 3 GHz.
- > It has 291 million transistors.
- > It has 64 KB of L1 cache per core and 4 MB of L2 cache.
- > It is launched in three different versions:
 - > Intel Core 2 Duo
 - > Intel Core 2 Quad
 - > Intel Core 2 Extreme

28

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL CORE I7




- > Introduced in 2008.
- > It is a 64-bit μ P.
- > It has 4 physical cores.
- > Its clock speed is from 2.66 GHz to 3.33 GHz.
- > It has 781 million transistors.
- > It has 64 KB of L1 cache per core, 256 KB of L2 cache and 8 MB of L3 cache.

29

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL CORE I5



- > Introduced in 2009.
- > It is a 64-bit μ P.
- > It has 4 physical cores.
- > Its clock speed is from 2.40 GHz to 3.60 GHz.
- > It has 781 million transistors.
- > It has 64 KB of L1 cache per core, 256 KB of L2 cache and 8 MB of L3 cache.

30

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

INTEL CORE I3



- Introduced in 2010.
- It is a 64-bit μ P.
- It has 2 physical cores.
- Its clock speed is from 2.93 GHz to 3.33 GHz.
- It has 781 million transistors.
- It has 64 KB of L1 cache per core, 512 KB of L2 cache and 4 MB of L3 cache.

31

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com

Thank You 
Have a Nice Day

32

Gursharan Singh Tatla
mailto:gursharansingh.in

www.eazynotes.com